

THE <u>LEADER</u> IN HEAVY-DUTY COOLANT SERVICE SINCE 2000

2V-700 Coolant Extractor / Injector Engineered to be the

Right Tool for the Job ...

Eliminates Trapped Air
 Closed-loop Containment System
 Re-Use Your Coolant
 Improve Employee Safety
 Protect the Environment
 Improve Shop Cleanliness
 asy to Operate
 Save Time & Money
 Water Filter Option

Coolant Service is a SNAP

Technical Data

- **Operates off standard shop air**
- **No mechanical parts to service**
- Portable Easy to Share
- **Easy to use manifold controls**
- <u>Tank capacities:</u>
 18.5 Gal & 30 Gal
- ♦ <u>12 Foot Service Hose</u>
- Front Mounted Sight Tube
- <u>Typical Service Time:</u> Flow rate: 2.5 gal / min Transfer time: avg 4-6 min's
- ◊ Uses Industry-Std Water Filter
- Air Extraction Kit evacuates trapped air from the top of the Cooling System



Designed to extract, contain and inject engine coolant from a vehicle's cooling

system, the 2V-700 gives service technicians the means to handle engine coolant

SAFELY and EFFICIENTLY



For more information contact:

Charles Sams - FluidXchange Email: cdsams@db-toolco.com www.**FLUIDXCHANGE**.com

> Phone: 931-738-3611 Fax: 931-738-3610



Quality System Registered to ISO 9001:2008

A Business Unit of Dunn & Bybee Tool Company

Volvo, Mack, & Prevost

These Vehicles come with factory installed quickdisconnect fittings.



Other Major OEM's come with CoolDrain-style Q/D Fittings or can easily be Retro-Fitted

4 npt sizes (1/2", 3/8", 1/4", & 1/8") for any application

